

[Home](#)
[Quick](#)
[Advanced](#)
[Pat Num](#)
[Help](#)

[Next List](#)
[Bottom](#)
[View Cart](#)

Results of Search in US Patent Collection db for:

Hits **1** through **50** out of **85**

Jump To

AN/"Excelitas"

Title

- 1 [11,139,635](#) **T** [Quantum well placement in a tunable VCSEL](#)
- 2 [11,092,426](#) **T** [Integrated optical coherence analysis system](#)
- 3 [10,985,546](#) **T** [Low-loss and fast acting solid-state breaker](#)
- 4 [10,951,009](#) **T** [Tunable VCSEL polarization control through dissimilar die bonding](#)
- 5 [10,951,007](#) **T** [Optically pumped tunable VCSEL employing geometric isolation](#)
- 6 [10,788,678](#) **T** [High brightness solid state illumination system for fluorescence imaging and analysis](#)
- 7 [10,730,072](#) **T** [Dispensing and ultraviolet \(UV\) curing with low backscatter](#)
- 8 [10,544,921](#) **T** [Luminaire with independently-controllable focus-tunable lenses](#)
- 9 [10,504,714](#) **T** [Dual parabolic laser driven sealed beam lamp](#)
- 10 [10,497,555](#) **T** [Laser driven sealed beam lamp with improved stability](#)
- 11 [10,267,563](#) **T** [System, method, and adjustable lamp head assembly, for ultra-fast UV curing](#)
- 12 [10,186,416](#) **T** [Apparatus and a method for operating a variable pressure sealed beam lamp](#)
- 13 [10,186,414](#) **T** [Dual parabolic laser driven sealed beam lamps](#)
- 14 [10,166,402](#) **T** [Visible light photo-disinfection patch](#)
- 15 [10,161,725](#) **T** [Initiator](#)
- 16 [10,109,473](#) **T** [Mechanically sealed tube for laser sustained plasma lamp and production method for same](#)
- 17 [10,082,658](#) **T** [High power microscopy illumination system with liquid cooled solid state light source \(SSLS\) unit](#)
- 18 [10,057,973](#) **T** [Electrodeless single low power CW laser driven plasma lamp](#)
- 19 [10,057,508](#) **T** [Illumination device with integrated thermal imaging sensor](#)
- 20 [10,018,510](#) **T** [Motion and presence detector](#)
- 21 [10,008,378](#) **T** [Laser driven sealed beam lamp with improved stability](#)
- 22 [10,003,171](#) **T** [Sealed laser diode heat sink module](#)
- 23 [9,979,281](#) **T** [Apparatus and method for dynamic adjustment of the bandwidth of a power converter](#)

[Home](#)
[Quick](#)
[Advanced](#)
[Pat Num](#)
[Help](#)